ELKAY SPECIFICATIONS

ezH2O® VR Mechanical Bottle Filling Station w/Integral Soft Sides® Ftn+Mounting Plate Filtered Non-Refrig. Stainless
Model LZVRSM-EDFPV217D1LK

PRODUCT SPECIFICATIONS

ezH2O® VR Mechanical Bottle Filling Station w/Integral Soft Sides® Ftn+Mounting Plate Filtered Non-Refrig. Stainless. Features shall include Ambient Water, Vandal Resistant, Mechanically Activated, Includes Back Plate, Laminar Flow, New Offering. Furnished with Vandal Resistant bubbler. Mechanical Bottle Filler Button with Mechanical Front Bubbler Button activation. Product shall be Wall Mount (Inwall Frame/Plate), for Indoor + Outdoor applications, serving 2 station(s).

Special Features:	Ambient Water, Vandal Resistant, Mechanically Activated, Includes Back Plate, Laminar Flow, New Offering
Finish:	Stainless Steel (S)
Power:	No Electrical Required
Bubbler Style:	Vandal Resistant
Activation by:	Mechanical Bottle Filler Button with Mechanical Front Bubbler Button
Mounting Type:	Wall Mount (Inwall Frame/Plate)
Chilling Capacity:	Non-refrigerated
Dimensions (L x W x H):	38-1/2" x 19-3/8" x 34-5/8"
Approx. Shipping Weight:	118 lbs.
Installation Location++:	Indoor + Outdoor
No. of Stations Served:	2

++When used in non-temperature controlled environments, unit(s) must be adequately winterized and/or protected from extreme heat to prevent damage where climates dictate.

Special Note: When used in non-temperature-controlled environments, unit(s) must be adequately winterized and/or protected from extreme heat to prevent damage where climates dictate. The filters are certified for water temperatures up to 100°F.

- Mechanically-Activated unit continues to supply water in event of service disruptions.
- Standard Filter Included: Filter is tested and certified to NSF/ANSI 42, 53, 372 and 401 for the reduction of lead, microplastics, Class 1 particulate, cysts, and chlorine taste and odor. 3,000 gallon capacity or 1 year after installation.
- Laminar flow provides clean fill with minimal splash.

Included with Product: **Bottle Filler (VRCSM214C), Fountain Only (EDFPV217LSM), Wall Plate (WSMP20)**

Ships in one box.

A Century of Tradition and Quality.
For more than 100 years, Elkay has been making innovative products and providing exceptional customer care. We take pride in offering plumbing products that make life easier, inspire change and leave the world a better place.

BUILT IN USA OF DOMESTIC AND FOREIGN PARTS

PRODUCT COMPLIANCE

ADA & ICC A117.1
ASME A112.19.3/CSA B45.4
NSF/ANSI 42, 53, 61 (Q≤1), 372 (lead free), & 401

IAPMO R&T

Complies with ADA & ICC A117.1 accessibility requirements when installed according to the requirements outlined in these standards. Installation may require additional components and/or construction features to be fully compliant. Consult the local Authority Having Jurisdiction if necessary.
Installation Instructions (PDF) - 2000001657
Installation Instructions (PDF) - 97696C

Water Systems are warranted for 12 months from date of installation. **Warranty pertains to drinking water applications only. Non-drinking water applications are not covered under warranty.**

Warranty (PDF)

PART:_____QTY: _____

PROJECT:_____

CONTACT:_____

DATE:_____

NOTES:_____

APPROVAL:_____

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.

Elkay REV 01142026
LZVRSM-EDFPV217D1LK
1-800-260-6640 | SVtechservice@Elkay.com
Patent zurn-elkay.com/patents
© 2026   Page 1
LZVRSM-EDFPV217D1LK_spec.pdf

ELKAY
SPECIFICATIONS

ezH2O® VR Mechanical Bottle Filling Station w/Integral Soft Sides®
Ftn+Mounting Plate Filtered Non-Refrig. Stainless
Model LZVRSM-EDFPV217D1LK

Optional Accessories

51300C	WaterSentry® Lead + Microplastics NSF/ANSI Certified 3000 Gal 12 Month Filter Spec Sheet (PDF)	
ACCESS12X38-5	Stainless Steel Access Panel for Bi-Level Architectural Fountains Spec Sheet (PDF)	
97258C	Cane Apron for Contour™ & Soft Sides® Models Black Spec Sheet (PDF)	

Elkay REV 01142026
LZVRSM-EDFPV217D1LK

1-800-260-6640 | SVtechservice@Elkay.com
Patent zurn-elkay.com/patents

© 2026   Page 2
LZVRSM-EDFPV217D1LK_spec.pdf

ELKAY
SPECIFICATIONS

ezH2O® VR Mechanical Bottle Filling Station w/Integral Soft Sides® Ftn+Mounting Plate Filtered Non-Refrig. Stainless
Model LZVRSM-EDFPV217D1LK

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.

Elkay REV 01142026
LZVRSM-EDFPV217D1LK

1-800-260-6640 | SVtechservice@Elkay.com
Patent zurn-elkay.com/patents

© 2026   Page 3
LZVRSM-EDFPV217D1LK_spec.pdf